

Catalogue for Spindles

SS MOTORS

India Office

Plot no R 522 , Rabale MIDC, Navi Mumbai 400701

Contact person: Amit Gadkari

Cell No: 0919890205159

Email: sparkeaa@gmail.com

China Works

No.36 South of Industrial road, Jinan, China 250100

Contact person: Jessie

Mob: (86) 18806418289

Water cooled spindle motor 24000rpm

Model No.	Power (KW)	Voltage (V)	Current (A)	Frequency (HZ)	Dimension (D*L)mm	Collet
GDZ65-800	0.8	220	5	400	65*160	ER11
GDZ80-1.5	1.5	220	5	400	80*180	ER11/ER16
GDZ80/100-2.2	2.2	220	8	400	80/100*215	ER20
GDZ100-3	3	220/380	7/12	400	100*250	ER20
GDZ100-4	4	220/380	10/13	400	125*300	ER25
GDZ125-4.5	4.5	380	8	400	125*357	ER25
GDZ125-5.5	5	380	8	400	125*357	ER25



Air cooled spindle motor 18000rpm

Model type	Power (KW)	Voltage (V)	Current (A)	Frequency (HZ)	Dimension (L*W*H)mm	Collet
GDZ65F-800	0.8	220	4	400	220/65/65	ER11
GDZ93×8 2-1.5	1.5	220/380	6.8/3.8	300	248/82/82	ER20
GDZ93*82 -2.2	2.2	220/380	5.5/10	300	285/82/82	ER25
GDZ93×8 2-3.5	3.5	220/380	8.8/15	300	327/82/82	ER25
GDZ120× 103-4.5	4.5	380	9.5	300	328/103/103	ER32
GDZ120× 103-6	6	380	9.5	300	371/103/103	ER32



Water cooled Milling Spindle for metal,stone,glass

Model No.	Speed (RPM)	Power (KW)	Diameter (mm)	OVL (mm)	Collet
GDZ48-0.3	60000	0.3	48	154	ER8
GDZ58-0.8	42000	0.8	58	232	ER11
GDZ58-0.8	60000	0.8	58	232	ER11
GDZ62-0.8	24000	0.8	62	232	ER11
GDZ62-0.8	42000	0.8	62	232	ER11
GDZ62-0.8	60000	0.8	62	232	ER11
GDZ62-1.2	24000	1.2	62	252	ER11
GDZ62-1.2	60000	1.2	62	252	ER11
GDZ65-0.8	42000	0.8	65	185	ER11
GDZ65-1.2	42000	1.2	65	252	ER11
GDZ80-1.5	42000	1.5	80	180	ER11
GDZ80-1.5	36000	1.5	80	220	ER16
GDZ80-2.2	24000	2.2	80	285	ER16
GDZ85-2.2	24000	2.2	85	292	ER20
GDZ100-2.2	24000	2.2	100	299	ER20
GDZ105-3	24000	3	105	296	ER20
GDZ110-3.5	21000	3.5	110	339	ER20
GDZ120-4	18000	4	120	357	ER25
GDZ125-4.5	18000	4.5	125	357	ER25
GDZ140-5.5	16000	5.5	140		ER25
GDZ160-7.5	16000	7.5	160		ER32



Water cooled ATC Spindle motor

Spindle model	Speed (r/min)	Motor				Collet
		Power (KW)	Voltage (V)	Current (A)	Frequency (Hz)	
ST80-20-24Z/1.5	24000	1.5	220	5.4	400	ISO20
ST80-20-30Z/1.8	30000	1.8	220	6.4	500	ISO20
ST100-25-24Z/3.2	30000	3.2	380	6.4	500	ISO25
ST110-30-24Z/4.5	24000	4.5	380	9.2	800	BT30
ST110-30-30Z/5.5	18000	5.5	380	12	1000	BT30
ST125-30-24Z/6.5	24000	6.5	380	13.5	800	BT30
ST150-30-18Z/7.5	18000	7.5	380	14.9	600	BT30

